


10/534779

Rec'd T/PTO 14 MAY 2005

PCT/SE 03 / 0 1 7 7 0

#2

PRVPATENT- OCH REGISTRERINGSVERKET
Patentavdelningen**Intyg
Certificate**

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande Electrolux AB, Stockholm SE
Applicant (s)

(21) Patentansökningsnummer 0203436-1
Patent application number

(86) Ingivningsdatum 2002-11-19
Date of filing

Stockholm, 2003-11-19

För Patent- och registreringsverket
For the Patent- and Registration Office

Sonia André
Sonia André

Avgift
Fee

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

**PATENT- OCH
REGISTRERINGSVERKET**
SWEDEN

Postadress/Adress
Box 5055
S-102 42 STOCKHOLM

Telefon/Phone
+46 8 782 25 00
Vx 08-782 25 00

Telex
17978
PATOREG S

Telefax
+46 8 666 02 86
08-666 02 86

BEST AVAILABLE COPY

Case P-10157

Applicant: Aktiebolaget Electrolux, Stockholm

Motor driven tool such as a pole hedge trimmer, a pole saw or the like.

This invention relates to a motor driven tool such as a pole hedge trimmer, a pole saw or the like comprising a drive unit that via a shaft tube is connected to a cutting unit which is turnably secured to the shaft tube.

Hedge trimmers and saws of the type mentioned above are provided with shaft tubes of different lengths and are used for trimming small as well as large trees, hedges, bushes and the like. These tools, that are provided with a handle having necessary control means for operating the drive unit and a further handle placed at the shaft tube, make it possible to find a comfortable working position when trimming bushes and trees and hedges since i.a. the cutting unit can be turned with respect to the shaft tube. This means that the operator before the work starts can put the cutting unit in a suitable angular position in order to adapt the severing or cutting means to the working position of the operator. However, the tools of today are designed such that the adjustment means are placed in close vicinity of the cutting unit. This means that adjustment operation is complicated since the operator is forced to leave hold of one or both handles in order to reach the locking means. Then the cutting unit has to be turned by means of a special handle before it is locked in its new position. The locking means and the special handle are usually also placed such that there is a risk that the operator gets injured by the cutting or severing parts of the cutting unit.

The purpose of this invention is to create an arrangement simplifying the adjustment procedure whereby the operator can turn the cutting unit with respect to the shaft tube mainly with preserved grip about the handle parts. This is achieved by means of a device having the characteristics mentioned in the claims.

Several embodiments of the invention will now be described with reference to the accompanying drawings on which Fig. 1 is a perspective view of a pole hedge trimmer of the type in question, Fig. 2 is a perspective view of a first embodiment of the adjusting arrangement, Fig. 3 is a section through a part of the arrangement shown in Fig. 2, Fig. 4

is a section through another part of the arrangement shown in Fig. 2, Fig. 5 is a perspective view of a second embodiment of the adjustment arrangement, Fig. 6 is a side view of the locking arrangement shown in Fig. 5, Fig. 7 is a section on the line VII-VII in Fig. 6 whereas Fig. 8 is a further embodiment of the locking mechanism.

As appears from Fig. 1 the pole hedge cutter comprises a drive unit 11 which via a shaft tube 12 is connected to a cutting unit 13. The drive unit 11 can be of any type such as an internal combustion engine or an electric motor whose output shaft is connected to a drive shaft, not shown, that is placed within the shaft tube and that via a gear 14 is connected to the cutting unit. The shaft tube 12 has an inner handle 15 that is provided with throttle control means and additional control means for the drive unit and an outer handle 16 designed as a sleeve of grip friendly material. The cutting unit 13 in a conventional manner is provided with stationary, comb shaped knife protectors cooperating with corresponding knives arranged to move forwards/backwards and being driven by the drive shaft via the gear 14. The cutting unit 13 is by means of a turnable connection A supported by the shaft tube 12. The turnable connection comprises a braking and locking means L that can be released by means of a control means M arranged close to the outer handle.

According to the embodiment shown in Fig. 2 the control means M comprises a turnable handle designed as a sleeve 17 and arranged outside the shaft tube 12 close to the outer handle 16. The sleeve 17 that preferably is provided with an outer shell of grip friendly material is at one of its end provided with an outer gear rim 18, see Fig. 3, cooperating with a tube socket 19 provided with a gear rim engaging the gear rim 18. The tube socket 19 is turnably supported in a gear box 20 surrounding the gear mechanism. The tube socket 19 drives a turning rod 21 having one end which is wave shaped and slidably arranged in a pocket of the tube socket 19 such that the turning rod follows the turning motion of the gear wheel at the same time as it has the possibility to move in the axial direction. The other end 23 of the turning rod is threaded and inserted into a lug 24 serving as a nut at the turnable connection A. The end part of the turning rod that extends from the lug is arranged to act on a lever 25 which is a part of the locking mechanism L. The lever 25 is supported for turning motion about a stub shaft 26 and has an abutment surface 27 resting against one end of a sleeve 28 whose other end rests against a shoulder 29 which is a part of a clamp connection arranged at the bearing housing and comprising a clamping ring 30 surrounding a turning shaft, not shown, of the cutting unit. The clamping ring 30 also comprises a shoulder 31 in which a screw 32 is threaded the screw

being freely movable in a through hole in the shoulder 29 and being provided with a screw head 33 which is placed in the sleeve 28. Between the screw head 33 and the shoulder 29 there are several spring washers 34. In order to prevent branches from getting entangled between the shaft tube 12 and the turning rod 21 it is covered by a protecting shell 35 which is secured to the shaft tube.

The arrangement shown in Fig. 2-4 operates in the following manner. When the operator desires to change the position of the cutting unit the sleeve 17 is turned which means that the tube socket 19 follows the motion and acts on the turning rod such that it by means of its threaded engagement with the lug 24 is moved axially to the left in Fig. 4 and hence influences the lever 25. This means that the lever is turned clockwise about the stub shaft 26 until the abutting surface 27 does not abut the sleeve 28 any longer which means that the shoulder 29 moves to the left in the figure such that the clamp ring 30 looses its grip about the turning shaft of the cutting unit. Because of the force created by the screw 32 and the spring washers 34 on the shoulder 29 a certain grip about the turning shaft is maintained. By pressing the cutting unit 13 against the ground or some other kind of counter acting object, thereby overcoming the braking moment that the spring washers create, the angle of the cutting unit with respect to the shaft tube 12 can now be changed. Then the cutting unit 13 is locked by turning the sleeve 17 in the opposite direction which means that the lever 25 will press the sleeve 28 against the shoulder 29 such that the distance between the two shoulders 29, 31 decreases thereby locking the clamping ring 30 about the turning shaft of the cutting unit.

At the embodiment shown in Fig. 5-7 the control means M comprises an arm 39 which by means of a shaft 40 is turnably supported between two side walls 41 arranged on the shaft tube 41. The shaft 40 supports a pocket, not shown, which in the same manner as has been mentioned at the embodiments described above encloses one end of a turning rod 42 such that it can be moved axially at the same time as it is turned. The other end of the turning rod is threaded and inserted into a central, tube shaped, threaded opening 43 arranged in a screw 44 which is threaded into a bearing housing 45 surrounding the turning shaft, not shown, of the cutting unit. The bearing housing 45 is provided with a recess 46 directed towards the turning shaft and comprising a brake pad 47 movable in the radial direction. Between the brake pad 47 and the inner end of the screw 44 there are several spring washers 48 having a central opening in which the turning rod 42 is freely movable and arranged such that it abuts the brake pad 47.

The arrangement shown in Fig. 5-7 operates in the following manner. In order to adjust the angle of the cutting unit 13 with respect to the shaft tube 12 the arm 39 is acted on whereby the turning motion is transferred to the turning rod 42. This means that the turning rod by means of the engagement with the screw 44, which is stationary arranged in the brake drum, is moved axially towards the left in Fig. 7 such that the grip from the brake pad 47 on the cutting unit turning shaft, which is inserted in the surrounding bearing housing 45, ceases. Because of the spring force created by the spring washers on the brake pad 47 a certain braking moment on the turning shaft of the cutting unit is retained. This means that the operator can then push the cutting unit against a suitable counter acting object for instance the ground, in order to achieve a force by means of which the cutting unit can be turned with respect to the shaft tube. In order to lock the cutting unit in the new position the arm 39 is moved back to its original position which means that the turning rod will move towards the right in Fig. 6 and thereby push the brake pad 47 against the turning shaft. In order to set a suitable braking moment when the locking function is not activated the screw 44 can be turned such that the force created by the spring washers 48 against the brake pad 47 is changed in a suitable way.

The embodiment of the locking mechanism L shown in Fig. 8, in the same manner as in the embodiments previously described, comprise a turning rod 50 which is influenced by a control means the end of the turning rod extending through a threaded through opening 51 of one of two legs 52, 53 of a U-shaped clamp shoe 54. The clamp shoe 57 partly surrounds two shoulders 55, 56 of a clamp ring 57 arranged on a bearing housing the clamp ring surrounding the turning shaft, not shown, of the cutting unit. The clamp shoe 57 has a slot 58 separating the two shoulders 55, 56 which are each provided with a through hole 59, 60 that are coaxial with the hole 51. The hole 59 is threaded and supports a screw 61 having one end abutting the end of the turning rod 50 and being partly threaded into the hole 59 whereas the screw runs freely through the hole 60. Further there are several spring washers 62 surrounding the screw 61 and placed between the shoulder 56 and the head 63 of the screw 61.

The locking mechanism described in Fig. 8, which might be used together with anyone of the control means M being previously described, operates in the following manner. When the locking function is to be loosed the control means is actuated such that the turning rod 59 becomes a turning motion which means that the turning rod because of the threaded engagement with the leg 52 of the clamp shoe 54 is moved towards the left in Fig. 8 with respect to the clamp shoe 54 such that the end of the turning rod 50 which

is freely movable in the opening 59 disengages the end of the screw 61. This means that the force which is transferred from the clamp shoe 54 via the leg 53 to the screw head 63 ceases such that the locking effect disappears at the same time as a certain grip remains between the turning shaft of the cutting unit and the bearing housing because of the clamping force created by the spring washers 62. The operator can then change the angle of the cutting unit 13 with respect to the shaft tube in a manner described previously after which the control means is influenced to again lock the cutting unit in the new position.

It should in this connection be pointed out that the combination of the control means M and the locking means L which has been shown in the embodiments is solely illustrative and that it of course is possible to use them in any combination. It should also be stressed that even if the embodiments mentioned above relate to hedge trimmers the described arrangements are applicable also for similar types of tools such as for pole saws (i.e. saws on which a guide plate with a saw chain is arranged at the upper part of the shaft tube and a drive unit is arranged at the lower part of the shaft tube) clearing saws and trimmers having cutting units with saw blades and cutting filaments.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181

Claims

1. Motor driven tool such as a pole hedge trimmer, a pole saw or the like comprising a drive unit (11) that via a shaft tube (12) is connected to a cutting unit (13) which is turnably secured to the tube **characterized in** that the turnable connection is under the influence of a locking mechanism (L) which from the normal working position of the operator can be released by means of a control means (M) arranged at the shaft tube (12).
2. Tool according to claim 1 **characterized in** that the control means (M) is arranged close to a handle (16) placed at the shaft tube (12)
3. Tool according to claim 1 or 2 **characterized in** that the locking mechanism (L) comprises a brake mechanism which by means of a force creating means (34,48,62) in the non locked position of the cutting unit (13) creates a braking force against outer forces that influences the cutting unit.
4. Tool according to any of the preceding claims **characterized in** that the locking mechanism (L) comprises a rod (21,42,50) which is mainly parallel to the shaft tube and by means of which a turning or forward/backwards movement is transferred from the control means (M) to a locking means being a part of the locking mechanism (L) possibly via a gear transmission.
5. Tool according to claim 4 **characterized in** that the control means (M) comprises a turnable sleeve (17) surrounding the shaft tube or a lever (39) turnably arranged at the shaft tube and being directly or indirectly connected to the rod (21,42,50).
6. Tool according to any of the preceding claims **characterized in** that the locking mechanism (L) comprises a clamp means.
7. Tool according to claim 6 **characterized in** that the clamp means completely or partly surrounds a shaft which is secured to the cutting unit.
8. Tool according to claim 7 **characterized in** that the clamp means comprises a clamp ring (30) having two shoulders (29,31) or the like being under the influence of a spring loaded screw connection (32) one of the shoulders (29) being movable towards the other shoulder (31) by means of a lever (25) arranged to be acted on by the control means (M) via a turning rod (23).

9. Tool according to claim 6 **characterized in** that the clamp means comprises a bearing housing (45) taking up said shaft and enclosing a brake pad (47) which is acted on by a turning rod (42) in order to lock the shaft in the bearing housing the brake pad being under the influence of a spring means (48).
10. Tool according to claim 9 **characterized in** that the spring characteristics of the spring means (48) is adjustable by means of a sleeve (44) which is threaded into the bearing housing (45) and having a through, threaded opening (43) through which the turning rod (42) extends and abuts the brake pad (47).
11. Tool according to claim 6 **characterized in** that the clamping means comprises a clamp ring (57) enclosing the shaft and having two shoulders (55,56) which are partly surrounded by a U-shaped clamp shoe (54) having one leg (52) with a through opening (51) through which a threaded turning rod (50) is inserted the opening being coaxial with a through opening (59,60) in each shoulder (55,56) and receiving a spring loaded screw (60) arranged to be influenced by the other leg (53) the end of the screw (60) normally abutting the end of the turning rod (50).

11-19-02

Abstract (Fig. 1)

This invention relates to a motor driven tool such as a pole hedge trimmer, a pole saw or the like comprising a drive unit (11) that via a shaft tube (12) is connected to a cutting unit (13) which is turnably secured to the tube. The turnable connection is under the influence of a locking mechanism (L) which from the normal working position of the operator can be released by means of a control means (M) arranged at the shaft tube (12).

11-19





Fig 1

The diagrams illustrate the steps of a bubble sort algorithm on the list [1, 2, 3, 4, 5, 6, 7]:

- Initial state: 1, 2, 3, 4, 5, 6, 7
- Comparison between 1 and 2: 1, 2, 3, 4, 5, 6, 7
- Comparison between 2 and 3: 1, 2, 3, 4, 5, 6, 7
- Comparison between 3 and 4: 1, 2, 3, 4, 5, 6, 7
- Comparison between 4 and 5: 1, 2, 3, 4, 5, 6, 7
- Comparison between 5 and 6: 1, 2, 3, 4, 5, 6, 7
- Comparison between 6 and 7: 1, 2, 3, 4, 5, 6, 7

0203434-1






Fig 3




Fig 4

0203434-1

PRV02-11-10




Fig. 5



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.